

PRODUCT CERTIFICATE



Industrial / OTR Tyres

E-3/L-3 ROCK GRIP ME3 456

ROCK GRIP ME3 456 is a wide base bias tyre designed for load carrying earth mover tyre which also very much suitable for wheel Loader. The tyre is suitable for medium haul application with moderate speed and load. Strong casing , low heat build up & cut resistance compound ensure good life and reliability.



WHEEL LOADER



ARTICULATED DUMP TRUCK



LOAD HAUL DUMPER



DOZER



DUMP TRUCK

Salient Features

Feature	Advantage	Benefit
'S' angled lugs	Balanced traction	Suitable for both in road and off road application
High strength casing materials	Suitable for higher load application	High stability during turning
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Recommended Load, kgs.				
				SW	OD					Inflation Pressure	Speed, km/h		Inflation Pressure	Speed, km/h
											Earth Mover Application			
				mm	mm					mm	mm	Bar	40	50
17.5-25	TL	14.00/15	-	445.0	1348.0	635.0	3988.0	16	158B/177A2	3	4890	4250	4.8	7300

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Recommended Load, kgs.				
				SW	OD					Inflation Pressure	Speed, km/h		Inflation Pressure	Speed, km/h
											Earth Mover Application			
				mm	mm					mm	mm	Bar	40	50
17.5-25	TL	14.00/15	-	445.0	1348.0	635.0	3988.0	20	164B/181A2	4	5750	5000	5.7	8250