

# PRODUCT CERTIFICATE



## Industrial / OTR Tyres

**L-4 / L-5 THE BEAST ML2 482 HD**

**ML2 482 HD** is suitable for tuff road condition in off high way construction application. It's extra mass on tread and open shoulder ensures proper traction and relief from obstruction. Its extra strong casing & special compound assure extended life and higher productivity.



BACKHOE



SKIDSTEER



DOZER

## Salient Features

Feature	Advantage	Benefit
Centre mass & open shoulder design	Better traction	Enhanced stability & self cleaning
Special RIM protector	Resist impact	Control damage
High strength casing materials	Strong casing	High stability during turning
Chip and cut resistant	Resistance to wear and tear	Extended mileage & durability

## Technical Data

Size	Type	Recommended Rim	Alternate Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR	Load Index / Speed Symbol	Inflation Pressure	Recommended Load, kgs				
				SW	OD						Speed, km/h				
				mm	mm						Free Rolling				
											Bar	10	15	25	30
10-16.5	TL	8.25	-	267	790	356	2285	12	138A2	2.8	2090	1670	1520	1420	
										3.1	2219	1777	1620	1510	
										3.4	2360	1890	1720	1610	