

Aggressive R4 pattern designed to maximize traction in soft underfoot conditions. Ideal for use on graders, loaders and earthmovers.

- ▶ Heavy-duty bias construction maximizes traction and flotation
- ▶ Wear and cut-resistant tread compound
- ▶ Self-cleaning tread design



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (lbs/kg)	INFLATION PRESSURE	L.C.C. (lbs/kg)	INFLATION PRESSURE	L.C.C. (lbs/kg)	L.I.
				in	in	32nds	psi	5 mph	psi	30 mph	psi	25 mph	
				mm	mm	mm	KPa	10 kph	KPa	50 kph	KPa	40 kph	
15.5-25	12	TL	12.00/1.3	50.4	15.7	30	58	12300	36	7150	36	5840	149B/142A8/168A2
				1280	398	24	400	5600	250	3250	250	2650	
17.5-25	12	TL	14.00/1.5	53.9	17.2	31	51	13600	33	8050	29	6400	153B/145A8/171A2
				1370	437	25	350	6150	225	3650	200	2900	
	16	TL	14.00/1.5	52.8	17.2	31	69	16100	44	9350	40	7400	158B/150A8/177A2
				1340	438	25	475	7300	300	4250	275	3350	
20.5-25	12	TL	17.00/2.0	58.3	20.6	35	36	14800	29	9900	25	7850	160B/152A8/174A2
				1481	523	28	250	6700	200	4500	175	3550	
	16	TL	17.00/2.0	58.8	20.7	35	51	18200	40	12000	32	8800	167B/156A8/181A2
				1494	526	28	350	8250	275	5450	225	4000	

